



author Yang Yingliang <yangyingliang@huawei.com> 2022-10-31 20:13:40 +0800
committer Greg Kroah-Hartman <gregkh@linuxfoundation.org> 2022-11-10 17:57:51 +0100
commit [2ff6b669523d3b3d253a044fa9636a67d0694995](#) (patch)
tree [c7ac2a1ffe50719496eae5f6272d5cee3af625ad](#)
parent [b13be5e852b03f376058027e462fad4230240891](#) (diff)
download [linux-2ff6b669523d3b3d253a044fa9636a67d0694995.tar.gz](#)

diff options

context:

3 ▼

space:

include ▼

mode:

unified ▼

mISDN: fix possible memory leak in mISDN_register_device()

[Upstream commit e7d1d4d9ac0dfa40be4c2c8abd0731659869b297]

Afer commit 1fa5ae857bb1 ("driver core: get rid of struct device's bus_id string array"), the name of device is allocated dynamically, add put_device() to give up the reference, so that the name can be freed in kobject_cleanup() when the refcount is 0.

Set device class before put_device() to avoid null release() function WARN message in device_release().

Fixes: 1fa5ae857bb1 ("driver core: get rid of struct device's bus_id string array")

Signed-off-by: Yang Yingliang <yangyingliang@huawei.com>

Signed-off-by: David S. Miller <davem@davemloft.net>

Signed-off-by: Sasha Levin <sashal@kernel.org>

Diffstat

```
-rw-r--r-- drivers/isdn/mISDN/core.c 5
```

1 files changed, 3 insertions, 2 deletions

diff --git a/drivers/isdn/mISDN/core.c b/drivers/isdn/mISDN/core.c

index a41b4b26459412..7ea0100f218a04 100644

--- a/drivers/isdn/mISDN/core.c

+++ b/drivers/isdn/mISDN/core.c

```
@@ -233,11 +233,12 @@ mISDN_register_device(struct mISDNdevice *dev,  
     if (debug & DEBUG_CORE)  
         printk(KERN_DEBUG "mISDN_register %s %d\n",  
                dev_name(&dev->dev), dev->id);  
+     dev->dev.class = &mISDN_class;  
+  
     err = create_stack(dev);  
     if (err)  
         goto error1;  
  
-     dev->dev.class = &mISDN_class;  
     dev->dev.platform_data = dev;  
     dev->dev.parent = parent;  
     dev_set_drvdata(&dev->dev, dev);  
@@ -249,8 +250,8 @@ mISDN_register_device(struct mISDNdevice *dev,  
  
error3:  
     delete_stack(dev);
```

```
-         return err;
error1:
+         put_device(&dev->dev);
        return err;

}
```