



author Yang Yingliang <yangyingliang@huawei.com> 2022-10-31 20:13:40 +0800
committer Greg Kroah-Hartman <gregkh@linuxfoundation.org> 2022-11-10 15:47:21 +0100
commit [080aabfb29b2ee9cbb8894a1d039651943d3773e](#) (patch)
tree [0c8cc8712e26dbeecf5656e03af2243a508e0a51](#)
parent [bbc03d74e641e824754443b908454ca9e203773e](#) (diff)
download [linux-080aabfb29b2ee9cbb8894a1d039651943d3773e.tar.gz](#)

diff options

context: ▼
space: ▼
mode: ▼

mISDN: fix possible memory leak in mISDN_register_device()

[Upstream commit e7d1d4d9ac0dfa40be4c2c8abd0731659869b297]

Afer commit 1fa5ae857bb1 ("driver core: get rid of struct device's bus_id string array"), the name of device is allocated dynamically, add put_device() to give up the reference, so that the name can be freed in kobject_cleanup() when the refcount is 0.

Set device class before put_device() to avoid null release() function WARN message in device_release().

Fixes: 1fa5ae857bb1 ("driver core: get rid of struct device's bus_id string array")
Signed-off-by: Yang Yingliang <yangyingliang@huawei.com>
Signed-off-by: David S. Miller <davem@davemloft.net>
Signed-off-by: Sasha Levin <sasha@kernel.org>

Diffstat

```
-rw-r--r-- drivers/isdn/mISDN/core.c 5
```

1 files changed, 3 insertions, 2 deletions

diff --git a/drivers/isdn/mISDN/core.c b/drivers/isdn/mISDN/core.c
index f5a06a6fb297f5..5cd53b2c47c755 100644

--- a/drivers/isdn/mISDN/core.c

+++ b/drivers/isdn/mISDN/core.c

```
@@ -242,11 +242,12 @@ mISDN_register_device(struct mISDNdevice *dev,  
    if (debug & DEBUG_CORE)  
        printk(KERN_DEBUG "mISDN_register %s %d\n",  
                dev_name(&dev->dev), dev->id);  
+    dev->dev.class = &mISDN_class;  
+  
    err = create_stack(dev);  
    if (err)  
        goto error1;  
  
-    dev->dev.class = &mISDN_class;  
    dev->dev.platform_data = dev;  
    dev->dev.parent = parent;  
    dev_set_drvdata(&dev->dev, dev);  
@@ -258,8 +259,8 @@ mISDN_register_device(struct mISDNdevice *dev,  
  
error3:  
    delete_stack(dev);
```

```
-         return err;
error1:
+         put_device(&dev->dev);
         return err;

    }
```