



index : kernel/git/stable/linux.git

Linux kernel stable tree

master switch

Stable Group

about summary refs log tree commit diff stats

log msg search

author Xiongfeng Wang <wangxiongfeng2@huawei.com> 2022-11-14 16:31:00 +0800
committer Greg Kroah-Hartman <gregkh@linuxfoundation.org> 2022-11-26 09:24:48 +0100
commit a99a547658e5d451f01ed307426286716b6f01bf (patch)
tree 56ea88835c3866f0185ad6b6687939dbdf171ef
parent 4a1b6f7839d3571d37ce344abdf60283298f6c83 (diff)
download [linux-a99a547658e5d451f01ed307426286716b6f01bf.tar.gz](#)

diff options

context: 3
space: include
mode: unified

mmc: sdhci-pci: Fix possible memory leak caused by missing pci_dev_put()

commit 222cf0118aa68687ace74aab8fdf77ce8fb7e6 upstream.

pci_get_device() will increase the reference count for the returned pci_dev. We need to use pci_dev_put() to decrease the reference count before amd_probe() returns. There is no problem for the 'smbus_dev == NULL' branch because pci_dev_put() can also handle the NULL input parameter case.

Fixes: 659c9bc114a8 ("mmc: sdhci-pci: Build o2micro support in the same module")

Signed-off-by: Xiongfeng Wang <wangxiongfeng2@huawei.com>

Cc: stable@vger.kernel.org

Link: <https://lore.kernel.org/r/20221114083100.149200-1-wangxiongfeng2@huawei.com>

Signed-off-by: Ulf Hansson <ulf.hansson@linaro.org>

Signed-off-by: Greg Kroah-Hartman <gregkh@linuxfoundation.org>

Diffstat

-rw-r--r--	drivers/mmc/host/sdhci-pci-core.c	2
------------	---	---

1 files changed, 2 insertions, 0 deletions

```
diff --git a/drivers/mmc/host/sdhci-pci-core.c b/drivers/mmc/host/sdhci-pci-core.c
index 65e61cdac118de..8736e04fa73cce 100644
--- a/drivers/mmc/host/sdhci-pci-core.c
+++ b/drivers/mmc/host/sdhci-pci-core.c
@@ -1818,6 +1818,8 @@ static int amd_probe(struct sdhci_pci_chip *chip)
}
}

+ pci_dev_put(smbus_dev);
+
if (gen == AMD_CHIPSET_BEFORE_ML || gen == AMD_CHIPSET_CZ)
chip->quirks2 |= SDHCI_QUIRK2_CLEAR_TRANSFERMODE_REG_BEFORE_CMD;
```