



author Cong Wang <xiyou.wangcong@gmail.com> 2025-04-17 11:47:30 -0700
committer Greg Kroah-Hartman <gregkh@linuxfoundation.org> 2025-05-02 07:50:44 +0200
commit 3aa852e3605000d5c47035c3fc3a986d14ccfa9f (patch)
tree 6bf8dbdd6638bc2372d471496f52a9d0893a9fe4
parent 4f435c1f4c48ff84968e2d9159f6fa41f46cf998 (diff)
download [linux-3aa852e3605000d5c47035c3fc3a986d14ccfa9f.tar.gz](#)

diff options

context: 3 ▼
space: include ▼
mode: unified ▼

net_sched: hfsc: Fix a UAF vulnerability in class handling

[Upstream commit 3df275ef0a6ae181e8428a6589ef5d5231e58b5c]

This patch fixes a Use-After-Free vulnerability in the HFSC qdisc class handling. The issue occurs due to a time-of-check/time-of-use condition in `hfsc_change_class()` when working with certain child qdiscs like `netem` or `codel`.

The vulnerability works as follows:

1. `hfsc_change_class()` checks if a class has packets (`q.qlen != 0`)
2. It then calls `qdisc_peek_len()`, which for certain qdiscs (e.g., `codel`, `netem`) might drop packets and empty the queue
3. The code continues assuming the queue is still non-empty, adding the class to `vttree`
4. This breaks HFSC scheduler assumptions that only non-empty classes are in `vttree`
5. Later, when the class is destroyed, this can lead to a Use-After-Free

The fix adds a second queue length check after `qdisc_peek_len()` to verify the queue wasn't emptied.

Fixes: 21f4d5cc25ec ("net_sched/hfsc: fix curve activation in `hfsc_change_class()`")

Reported-by: Gerrard Tai <gerrard.tai@starlabs.sg>

Reviewed-by: Konstantin Khlebnikov <koc9i@gmail.com>

Signed-off-by: Cong Wang <xiyou.wangcong@gmail.com>

Reviewed-by: Jamal Hadi Salim <jhs@mojatatu.com>

Link: <https://patch.msgid.link/20250417184732.943057-2-xiyou.wangcong@gmail.com>

Signed-off-by: Jakub Kicinski <kuba@kernel.org>

Signed-off-by: Sasha Levin <sashal@kernel.org>

Diffstat

```
-rw-r--r-- net/sched/sch_hfsc.c 9
```

1 files changed, 7 insertions, 2 deletions

diff --git a/net/sched/sch_hfsc.c b/net/sched/sch_hfsc.c

index 880c5f16b29ccf..90801b6fe2b088 100644

--- a/net/sched/sch_hfsc.c

+++ b/net/sched/sch_hfsc.c

@@ -958,6 +958,7 @@ hfsc_change_class(struct Qdisc *sch, u32 classid, u32 parentid,

```
    if (cl != NULL) {  
        int old_flags;
```

```

+         int len = 0;

+         if (parentid) {
+             if (cl->cl_parent &&
@@ -988,9 +989,13 @@ hfsc_change_class(struct Qdisc *sch, u32 classid, u32 parentid,
+             if (usc != NULL)
+                 hfsc_change_usc(cl, usc, cur_time);

+         if (cl->qdisc->q qlen != 0)
+             len = qdisc_peek_len(cl->qdisc);
+         /* Check queue length again since some qdisc implementations
+          * (e.g., netem/codel) might empty the queue during the peek
+          * operation.
+          */
+         if (cl->qdisc->q qlen != 0) {
-             int len = qdisc_peek_len(cl->qdisc);
-
+             if (cl->cl_flags & HFSC_RSC) {
+                 if (old_flags & HFSC_RSC)
+                     update_ed(cl, len);

```