

Commit 52a078d

[Browse files](#)

jipin authored and huozi committed 3 weeks ago

Update middleware request header ([#77201](#))

This just adds an additional header to our internal filtering list for middleware.

next-15-2 · v15.2.4 v15.2.3

1 parent [4698ad6](#) commit 52a078d Filter files...

- ✓ [packages/next/src/server](#)
- ✓ [lib](#)
 - [router-server.ts](#)
- ✓ [server-ipc](#)
 - [utils.ts](#)
- ✓ [web/sandbox](#)
 - [context.ts](#)
- ✓ [test/e2e/middleware-general/test](#)
 - [index.test.ts](#)

[4 files changed +35 -4 lines changed](#) Search within code

- ✓ [packages/next/src/server/lib/router-server.ts](#) [diff](#) [+7 -4](#) [blob](#) [raw](#) [...](#)

```
@@ -166,10 +166,13 @@ export async function initialize(opts: {  
166   166     renderServer.instance =  
167   167       require('./render-server') as typeof import('./render-server')  
168   168  
169   -     const allowedOrigins = [  
170   -       'localhost',  
171   -       ...(config.experimental.allowedDevOrigins || []),  
172   -     ]  
169   +     const randomBytes = new Uint8Array(8)  
170   +     crypto.getRandomValues(randomBytes)
```

```
171 +   const middlewareSubrequestId = Buffer.from(randomBytes).toString('hex')
172 + ;(globalThis as any)[Symbol.for('@next/middleware-subrequest-id')] =
173 +   middlewareSubrequestId
174 +
175 +   const allowedOrigins = ['localhost', ...(config.allowedDevOrigins || [])]
173 176     if (opts.hostname) {
174 177       allowedOrigins.push(opts.hostname)
175 178     }
....
```

▼ packages/next/src/server/lib/server-ipc/utils.ts ⌂ ⌁

+11 00000 ...

```
↑ @@ -57,5 +57,16 @@ export const filterInternalHeaders = (
57 57   if (INTERNAL_HEADERS.includes(header)) {
58 58     delete headers[header]
59 59   }
60 +
61 + // If this request didn't origin from this session we filter
62 + // out the "x-middleware-subrequest" header so we don't skip
63 + // middleware incorrectly
64 + if (
65 +   header === 'x-middleware-subrequest' &&
66 +   headers['x-middleware-subrequest-id'] !==
67 +   (globalThis as any)[Symbol.for('@next/middleware-subrequest-id')])
68 + ) {
69 +   delete headers['x-middleware-subrequest']
70 + }
60 71 }
61 72 }
```

▼ packages/next/src/server/web/sandbox/context.ts ⌂ ⌁

+4 00000 ...

```
↑ @@ -373,6 +373,10 @@ Learn More: https://nextjs.org/docs/messages/edge-dynamic-code-
evaluation`),
373 373       store.headers.get('x-middleware-subrequest') ?? ''
374 374     )
375 375   }
376 +   init.headers.set(
377 +     'x-middleware-subrequest-id',
378 +     (globalThis as any)[Symbol.for('@next/middleware-subrequest-id')]
379 +   )
376 380
377 381     const prevs =
378 382       init.headers.get(`x-middleware-subrequest`)? .split(':') || []
```

```
.... @@ -144,6 +144,19 @@ describe('Middleware Runtime', () => {
144   144     }
145   145   }
146   146
147 +   it('should filter request header properly', async () => {
148 +     const res = await next.fetch('/redirect-to-somewhere', {
149 +       headers: {
150 +         'x-middleware-subrequest':
151 +           'middleware:middleware:middleware:middleware',
152 +       },
153 +       redirect: 'manual',
154 +     })
155 +
156 +     expect(res.status).toBe(307)
157 +     expect(res.headers.get('location')).toContain('/somewhere')
158 +   })
159 +
147 160   it('should handle 404 on fallback: false route correctly', async () => {
148 161     const res = await next.fetch('/ssg-fallback-false/first')
149 162     expect(res.status).toBe(200)
```

....

Comments 0



Please [sign in](#) to comment.